

Technical data sheet

1950 siaspeed



MKP person responsible:	Colin Giger
Serie-Verantwortlicher:	Building Interior: Colin Giger Automotive: Colin Giger Aerospace: Colin Giger
Status:	Ok
Approval:	15.12.2020

Classification	
	Public series
Product type:	Coated abrasives
Main industries:	Automotive Aerospace Building Interior
Further industries:	Trucks Rail Marine Bus Wind Power Kitchens

Product profile		
Grit type:	Mixed grit with ceramic content Semi-friable aluminium oxide / blue-fired	40 – 80 P100 – P600
Grit range (total):	40; 60-600	P100 – P600 FEPA P / ISO 6344
Backing:	Paper	
Coating:	Electrostatic Electrostatic open	40 – P180 P220 – P600
bonding:	Resin over resin	
Special coating:	Stearate	from 80
Equipment:		

Properties		Technology
Removal rate:	10 - very high	- Offene Streuung - siafast - siasoft
Lifetime:	10 - very long	
Finishing:	7 - good	
Flexibility:	7 - flexible	
Contact pressure:		

Advantages	
Building Interior:	- A versatile all-round product - High performance for stock removal - Longest lifetime - Minimal clogging thanks to open coating in 220 - 600 grit range

Technical data sheet

1950 siaspeed









Advantages	
Automotive:	<ul style="list-style-type: none"> - Very high abrasive performance with a good finish - Performance-enhancing grit mix with ceramic corundum in 40 - 80 grit range - Minimal clogging thanks to open coating in 220 - 600 grit range - Extremely long lifetime - Lower abrasive consumption - Versatile all-round product with an attractive range of options
Aerospace:	<ul style="list-style-type: none"> - High-performance abrasives - High performance for stock removal - Longest lifetime - A versatile all-round product - Lower abrasive consumption - Homogeneous sanding finish

Applications	
Building Interior:	<ul style="list-style-type: none"> - Sanding out uneven areas such as scratches or marks
Automotive:	<ul style="list-style-type: none"> - Sanding off coatings and impurities - Sanding out unevenness at the edges of repaired surfaces - Flatting bodyfiller and composite materials - Fine sanding primer filler - Keying old and new lacquers
Aerospace:	<ul style="list-style-type: none"> - Keying polyesters and composites - Sanding out feather edges, flash rust and stone chips - Shaping of bodyfillers and primer fillers - Keying new components and factory primers - Sanding off of old varnish - Producing a matt finish on old and new lacquers for blending - Flatting bodyfiller and primer filler

Material			
Building Interior:	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;"> <ul style="list-style-type: none"> Dry wall lining boards Lacquers Mineral materials Plaster Primer filler Putty Wood Wood Wood </td> <td style="width: 50%; border: none;"> <ul style="list-style-type: none"> <input type="radio"/> Plastics <input type="radio"/> Dry wall lining boards <input checked="" type="radio"/> Paints <input checked="" type="radio"/> Solid surface material <input type="radio"/> Plaster <input checked="" type="radio"/> Primer filler <input checked="" type="radio"/> Putty <input checked="" type="radio"/> Hardwood <input checked="" type="radio"/> Softwood <input type="radio"/> Resinous wood </td> </tr> </table>	<ul style="list-style-type: none"> Dry wall lining boards Lacquers Mineral materials Plaster Primer filler Putty Wood Wood Wood 	<ul style="list-style-type: none"> <input type="radio"/> Plastics <input type="radio"/> Dry wall lining boards <input checked="" type="radio"/> Paints <input checked="" type="radio"/> Solid surface material <input type="radio"/> Plaster <input checked="" type="radio"/> Primer filler <input checked="" type="radio"/> Putty <input checked="" type="radio"/> Hardwood <input checked="" type="radio"/> Softwood <input type="radio"/> Resinous wood
<ul style="list-style-type: none"> Dry wall lining boards Lacquers Mineral materials Plaster Primer filler Putty Wood Wood Wood 	<ul style="list-style-type: none"> <input type="radio"/> Plastics <input type="radio"/> Dry wall lining boards <input checked="" type="radio"/> Paints <input checked="" type="radio"/> Solid surface material <input type="radio"/> Plaster <input checked="" type="radio"/> Primer filler <input checked="" type="radio"/> Putty <input checked="" type="radio"/> Hardwood <input checked="" type="radio"/> Softwood <input type="radio"/> Resinous wood 		

Material		
Automotive:	Composites Gelcoats Lacquers Lacquers Paints Plastics Plastics Primer filler Primers Primers Primers Putty	<ul style="list-style-type: none"> ● Glass-fibre reinforced plastic (GRP) ● Gelcoat polyester ● Paints ● Old lacquer ● Colour ● Plastics ● Acrylic glas ● Primer filler ● Primer coat ● Epoxy primer coat ● Cathodic dip primer coat ● Putty
Aerospace:	Acrylic glass (Plexiglass) Composites Gelcoats Lacquers Plastics Primers Primers Primers Putty	<ul style="list-style-type: none"> ● Colour ● Primer filler ● Old lacquer ● Acrylic glas ● Glass-fibre reinforced plastic (GRP) ● Gelcoat polyester ● Paints ● Plastics ● Primer coat ● Epoxy primer coat ● Cathodic dip primer coat ● Putty

Conversion forms	Upper conversion	Lower conversion
	Rolls	<ul style="list-style-type: none"> - jumbolino - Paper rolls - siafast rolls - siasoft rolls
	Strips	<ul style="list-style-type: none"> - siafast strips - siasoft strips
	Delta and polygons	<ul style="list-style-type: none"> - Delta and polygons
	Discs	<ul style="list-style-type: none"> - Daisy discs - siafast discs - siasoft discs - Various discs

Application	Superordinate group	Subgroup
	Portable machine sanding	random orbital sander
	Portable machine sanding	Orbital sander

Technical data sheet

1950 siaspeed



Application	Superordinate group	Subgroup
	Portable machine sanding	Delta sander
	Manual sanding	Manual sanding
	Manual sanding	hand sanding with sanding block
	Stationary machine sanding	Rolls
cut:	Dry applications	

Details	
No suitability for:	<ul style="list-style-type: none"> - glass sanding - Wet sanding - stone grinding
Sanding recommendation:	
Safety recommendation:	<ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication			
Claim:	For a perfect finish at full speed		
Copy:	The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.		
Image material:	Product Top View (PTV)	Front side:	ID
		Rear side:	ID
	Application image	Building Interior:	ID 342
		Automotive:	ID 8855
		Aerospace:	ID 9271
	Product show:		
Macro shot:			
Packaging image:			
Product group image:	ID 1656		

- Main application
- Secondary application